




CUSTOM SECTION INFLATABLE SEAL PROFILE



Inflated height (mm)	34	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		 INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1			
Cross-sectional area (mm²)	626				ISO 3302-1: 2014 E3			Drawn by Serhat Çınar		Approved by Arif Çınar			
Weight (kg/m)	0.814	0.0	1.5	0.40	Material Silicone rubber		Beykent Industrial Estate 141 Sakarya Street Buyukcekmece / Istanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com	Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission. info@cinarsilikon.com www.cinarsilikon.com		Revision No: 0		Scale: -	
INFLATION PRESSURE (bar)		1.5	2.5	0.50						Hardness: 60 Shore A Colour: Natural		Custom Section Inflatable Seal Profile	
Recommended	1.38	2.5	4.0	0.70									
Maximum	1.72	4.0	6.3	0.80									
MIN. BEND RADIUS (mm)		6.3	10.0	1.00									
		10.0	16.0	1.30									
Radially inward	185	16.0	25.0	1.60	Projection 			Profile No. 1742					
Radially outward	205	25.0	40.0	2.00									
Axial	420	40.0	63.0	2.50									
		63.0	100.0	3.20									
		100.0	-	3.2%									