





CHANNEL FIT INFLATABLE SEAL PROFILE



Inflated height (mm)	17.3	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1	
Cross-sectional area (mm²)	99				ISO 3302-1: 2014 E3				Drawn by Serhat Çınar		Approved by Arif Çınar
Weight (kg/m)	0.129	0.0	1.5	0.40	Material Silicone rubber		Beykent Industrial Estate 141 Sakarya Street Buyukcekmece / Istanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com	Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission. info@cinarsilikon.com www.cinarsilikon.com		Revision No: 0 Scale: - Channel Fit Inflatable Seal Profile Profile No. 3091	
INFLATION PRESSURE (bar)		1.5	2.5	0.50							
Recommended	0.69	2.5	4.0	0.70							
Maximum	0.69	4.0	6.3	0.80	Hardness: 60 Shore A Colour: Natural		Projection 				
MIN. BEND RADIUS (mm)		6.3	10.0	1.00							
Radially inward	60	10.0	16.0	1.30							
Radially outward	70	16.0	25.0	1.60							
Axial	70	25.0	40.0	2.00							
		40.0	63.0	2.50							
		63.0	100.0	3.20							
		100.0	-	3.2%							



Beykent Industrial Estate

141 Sakarya Street
Buyukcekmece / Istanbul
Turkey
+90 538 840 29 87

info@inflatablegaskets.com
www.inflatablegaskets.com

Prepared by Çınar Silikon
Mam. San. ve Tic. Ltd. Şti.
Reproduction or sharing
with third parties requires
prior written permission.

info@cinarsilikon.com
www.cinarsilikon.com