




FLEXIBLE SIDEWALL INFLATABLE SEAL PROFILE



Inflated height (mm)	21	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		 INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1			
Cross-sectional area (mm²)	105				ISO 3302-1: 2014 E3			Drawn by Serhat Çınar		Approved by Arif Çınar			
Weight (kg/m)	0.137	0.0	1.5	0.40	Material Silicone rubber		Beykent Industrial Estate 141 Sakarya Street Buyukcekmece / Istanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com	Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission.		Revision No: 0		Scale: -	
INFLATION PRESSURE (bar)		1.5	2.5	0.50						Hardness: 60 Shore A		Colour: Natural	
		2.5	4.0	0.70									
Recommended	1.03	4.0	6.3	0.80	Projection 					Flexible Sidewall Inflatable Seal Profile			
Maximum	1.03	6.3	10.0	1.00									
MIN. BEND RADIUS (mm)		10.0	16.0	1.30	Profile No. 4245								
		16.0	25.0	1.60									
Radially inward	110	25.0	40.0	2.00									
Radially outward	110	40.0	63.0	2.50									
Axial	150	63.0	100.0	3.20									
		100.0	-	3.2%									