




CUSTOM SECTION INFLATABLE SEAL PROFILE



Inflated height (mm)	36	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		 INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1		
Cross-sectional area (mm²)	662				ISO 3302-1: 2014 E3				Drawn by Serhat Çınar		Approved by Arif Çınar	
Weight (kg/m)	0.861	0.0	1.5	0.40	Material Silicone rubber							
INFLATION PRESSURE (bar)		1.5	2.5	0.50								
		2.5	4.0	0.70								
Recommended	0.97	4.0	6.3	0.80	Hardness: 60 Shore A Colour: Natural							
Maximum	1.38	6.3	10.0	1.00								
MIN. BEND RADIUS (mm)		10.0	16.0	1.30	Projection							
		16.0	25.0	1.60								
Radially inward	200	25.0	40.0	2.00								
Radially outward	200	40.0	63.0	2.50								
		63.0	100.0	3.20								
Axial	240	100.0	-	3.2%								
							Beykent Industrial Estate 141 Sakarya Street Buyukcekmece / Istanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com		Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission. info@cinarsilikon.com www.cinarsilikon.com		Revision No: 0 Scale: -	
									Custom Section Inflatable Seal Profile		Profile No. 4528	