




STEM FOOT INFLATABLE SEAL PROFILE



Inflated height (mm)	26	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		 INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1	
Cross-sectional area (mm²)	252				ISO 3302-1: 2014 E3				Drawn by Serhat Çınar		Approved by Arif Çınar
Weight (kg/m)	0.328	0.0	1.5	0.40	Material Silicone rubber				Revision No: 0	Scale: -	
INFLATION PRESSURE (bar)		1.5	2.5	0.50							
		2.5	4.0	0.70							
Recommended	0.55	4.0	6.3	0.80	Hardness: 60 Shore A Colour: Natural					Stem Foot Inflatable Seal Profile	
Maximum	0.83	6.3	10.0	1.00							
MIN. BEND RADIUS (mm)		10.0	16.0	1.30	Projection					Profile No.	6154
			16.0	25.0							
Radially inward	180	25.0	40.0	2.00							
Radially outward	150	40.0	63.0	2.50							
		63.0	100.0	3.20							
Axial	465	100.0	-	3.2%							
					Beykent Industrial Estate 141 Sakarya Street Buyukcekmece / Istanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com			Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission. info@cinarsilikon.com www.cinarsilikon.com			