




CUSTOM SECTION INFLATABLE SEAL PROFILE



Inflated height (mm)	73	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1	
Cross-sectional area (mm²)	1287				ISO 3302-1: 2014 E3				Drawn by Serhat Çınar		Approved by Arif Çınar
Weight (kg/m)	1.673	0.0	1.5	0.40	Material Silicone rubber						
INFLATION PRESSURE (bar)		1.5	2.5	0.50							
		2.5	4.0	0.70							
Recommended	0.69	4.0	6.3	0.80	Hardness: 60 Shore A Colour: Natural				Revision No: 0	Scale: -	
Maximum	1.03	6.3	10.0	1.00							
MIN. BEND RADIUS (mm)		10.0	16.0	1.30	Projection					Custom Section Inflatable Seal Profile	
		16.0	25.0	1.60							
Radially inward	370	25.0	40.0	2.00					Profile No.	8451	
Radially outward	450	40.0	63.0	2.50							
Axial	470	63.0	100.0	3.20							
		100.0	-	3.2%							
Beykent Industrial Estate 141 Sakarya Street Buyukcekmece / Istanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com							Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission. info@cinarsilikon.com www.cinarsilikon.com				