




FLEXIBLE SIDEWALL INFLATABLE SEAL PROFILE



Inflated height (mm)	23.3	Over	Nominal size Up to and including	Tolerance E3 +/-	Manufacturing tolerance		 INFLATABLE GASKETS INFLATABLE SEALING SOLUTIONS	Date 09.09.2026		Page A4 · 1/1			
Cross-sectional area (mm²)	114				ISO 3302-1: 2014 E3			Drawn by Serhat Çınar		Approved by Arif Çınar			
Weight (kg/m)	0.148	0.0	1.5	0.40	Material Silicone rubber		Beykent Industrial Estate 141 Sakarya Street Büyükcemece / İstanbul Turkey +90 538 840 29 87 info@inflatablegaskets.com www.inflatablegaskets.com	Prepared by Çınar Silikon Mam. San. ve Tic. Ltd. Şti. Reproduction or sharing with third parties requires prior written permission.		Revision No: 0		Scale: -	
INFLATION PRESSURE (bar)		1.5	2.5	0.50						Hardness: 60 Shore A		Colour: Natural	
	Recommended	0.69	2.5	4.0									
Maximum	1.03	4.0	6.3	0.80	Projection				Flexible Sidewall Inflatable Seal Profile				
MIN. BEND RADIUS (mm)		6.3	10.0	1.00									
	Radially inward	40	10.0	16.0	1.30								
Radially outward	50	16.0	25.0	1.60							Profile No. 8718		
	Axial	80	25.0	40.0									2.00
		40.0	63.0	2.50									
		63.0	100.0	3.20									
		100.0	-	3.2%									